



Jointing sleeve with cable gland IP68

- Two variants, screw-connection (1459904 & 1459903) and fast connection (1459905)
- Stationary laying of cables in cable ducts or suspended ceilings, stationary upper-plaster laying
- Quick and easy installation
- Suitable for narrow spaces
- 1459906 reduction sealing insert for 1459904

Specification

| | |
|---------------------------|---|
| MATERIAL ENCLOSURE | Polypropylene / (1459903) Polystyrene |
| INGRESS PROTECTION | IP68 - 5 bar (30 min) |
| COLOUR | Lightgrey RAL 7035 |
| FLAME PROTECTION | Glow wire test 750°C acc. to DIN EN 60695-2-1/1 (terminalblock 960°C) |
| HALOGEN-FREE | Yes |

Variants

| E-NUMBER | DESCRIPTION | FOR CABLE Ø MM | H MM | SW1 MM | SW2 MM | PCS/PACK |
|----------|--|----------------|------|--------|--------|----------|
| 1459904 | Terminal block 5x(1,5-2,5mm ²) | 9 - 17 | 134 | 27 | 29 | 15 |
| 1459903 | Terminal block 5x(1,5-6mm ²) | 10 - 18 | 165 | 32 | 33 | 10 |
| 1459905 | Splicing connector 3x(1,5-4mm ²) | 7 - 17 | 134 | 27 | 29 | 15 |
| 1459906 | Reducing sealing insert for smaller cable Ø | 7 - 12 | - | 0 | 0 | 25 |