



Multiple Sealing ring for Metric and PG

Assembled in "IP54 and IP55" plastic- and brass cable glands.

Specification

MATERIAL	SBR/NBR
TEMPERATURE RANGE	-30°C...+100°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

ARTICLE NO.	SIZE	DA MM	DI MM	DI1 MM	DI2 MM	DI3 MM	H MM	PCS/PACK
309 UG	M12, M16, PG9/15,2	13.3	5	7.5	10	-	5,5	100
311 UG	M16, M20, PG11/18,6	16.5	7.5	10	12.5	-	6	100
313 UG	M20, PG13,5/20,4	18.3	7.5	10	12.5	-	6	100
316 UG	M20, M25, PG16/22,5	20.4	7.5	10	12.5	15	7	100
321 UG	M25, PG21/28,3	25.9	10	13	16	19	8	100
329 UG	M32, M40, PG29/37,0	34.7	18	21	24	27	9,5	50
336 UG	M40, M50, PG36/47,0	44.7	24	27	30	33	12	50
342 UG-30	M50, PG42/54,0	51.7	30	33	36	39	14	25
348 UG-36	M63, PG48/59,3	56.9	36	39	42	45	14	25