



Adapter Brass Metric - PG

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
O-RING	Nitrile Rubber NBR
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-30°C...+100°C
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	INTERNAL THREAD	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1476461	M16x1,5	PG7/12,5	5	8	17	19	100
1476462	M20x1,5	PG9/15,2	6	9	22	24,5	100
1476463	M25x1,5	PG9/15,2	7	10	27	30	100
1476464	M25x1,5	PG11/18,6	7	10	27	30	100
1476465	M25x1,5	PG13,5/20,4	7	10	27	30	100
1476466	M32x1,5	PG13,5/20,4	8	11	34	36	50
1476467	M32x1,5	PG16/22,5	8	11	34	36	50
1476468	M32x1,5	PG21/28,3	8	11	34	36	50
1476469	M40x1,5	PG16/22,5	8	12	43	46	25
1476470	M40x1,5	PG21/28,3	8	12	43	46	25
1476471	M40x1,5	PG29/37,0	8	12	43	46	25
1476472	M50x1,5	PG21/28,3	9	13	55	60	25
1476473	M50x1,5	PG29/37,0	9	13	55	60	10
1476474	M50x1,5	PG36/47,0	9	13	55	60	10
1476475	M63x1,5	PG29/37,0	10	14	65	70	10
1476476	M63x1,5	PG36/47,0	10	14	65	70	10
1476477	M63x1,5	PG42/54,0	10	14	65	70	10