



Adapter Brass PG - Metric

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
TEMPERATURE RANGE	-60°C...+200°C
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	INTERNAL THREAD	L MM	L1 MM	DI MM	H MM	L2 MM	SW1 MM	E1 MM	PCS/PACK
1476490	PG7/12,5	M12x1,5	5	5.5	9	15	7.5	14	15.5	100
1476491	PG9/15,2	M16x1,5	6	5.5	12.2	16	7.5	19	21	100
1476492	PG11/18,6	M16x1,5	6	5.5	13	16	7.5	22	24.5	100
1476493	PG13,5/20,4	M20x1,5	6.5	6.5	16	17,5	8.5	24	26	100
1476494	PG16/22,5	M20x1,5	6.5	8.5	18.5	17,5	7.5	27	29	100
1476495	PG16/22,5	M25x1,5	6.5	7.5	18.5	18,5	9.5	30	33.5	100
1476496	PG21/28,3	M25x1,5	7	7.5	23	19	9.5	32	35.5	100
1476497	PG21/28,3	M32x1,5	7	8.5	23	20	10.5	36	39	100
1476498	PG29/37,0	M40x1,5	8	8.5	32	21	10.5	43	46	50
1476499	PG36/47,0	M50x1,5	9	9	42	23	11	55	60	25
1476500	PG42/54,0	M63x1,5	10	10	48	25	12	65	70	10

