



Cable Gland Brass IP54 increased anchorage Metric

E-14 760 82 with one-part sealing ring 5-7mm.

- Increased anchorage
- Multiple perforations for wide sealing range

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
SEALING RING	Perbunan NBR
INGRESS PROTECTION	IP54
TEMPERATURE RANGE	-20°C...+80°C
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW1 MM	SW2 MM	E1 MM	E2 MM	PCS/PACK
1476082	M12x1,5	5 - 7	5	27,3	14	16	15.5	17.5	50
1476083	M16x1,5	5 - 10	5	28,7	18	19	20	20.3	50
1476084	M20x1,5	7,5 - 12	6	32,2	22	22	24.4	24	50
1476085	M20x1,5	7,5 - 14	6	33,7	22	24	24.4	26.4	50
1476086	M20x1,5	7,5 - 15	6	34,8	24	27	26.7	30	50
1476087	M25x1,5	10 - 19,5	7	38,7	30	34	33.5	37.8	25
1476088	M32x1,5	18 - 26,5	8	42,3	40	42	43.5	46.5	25
1476089	M40x1,5	24 - 32	8	49	50	52	54	56	10
1476090	M50x1,5	30 - 42	9	52,7	57	62	60	67.5	5
1476091	M63x1,5	36 - 46	10	54,7	66	68	70	74	5