



Cable Gland brass IP54 multiple perforations Metric

E-14 760 70 with one-part sealing ring 5-7mm.

- Multiple perforations for wide sealing range

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
SEALING RING	Perbunan 80
INGRESS PROTECTION	IP54
TEMPERATURE RANGE	-20°C...+80°C
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW1 MM	SW2 MM	E1 MM	E2 MM	PCS/PACK
1476070	M12x1,5	5 - 7	5	20,5	14	13	15.5	14.3	100
1476071	M16x1,5	5 - 10	5	21,2	18	15	20	16.6	100
1476072	M20x1,5	7,5 - 12	6	23,4	22	18	24.4	20	50
1476073	M20x1,5	7,5 - 14	6	25	22	20	24.4	22.5	50
1476074	M20x1,5	7,5 - 14,5	6	26,1	24	22	26.7	24.4	50
1476075	M25x1,5	9 - 19,5	7	29,7	30	28	33.5	31.2	50
1476077	M32x1,5	18 - 27	8	32,7	40	37	43.5	41	25
1476078	M40x1,5	24 - 32	8	37,3	50	47	54	50.5	20
1476079	M50x1,5	30 - 42	9	42,5	57	54	60	59	10
1476080	M63x1,5	36 - 46	10	44,7	66	60	70	65	10