



Cable Gland Brass IP67 "WADI-Heat" Metric

For high temperature ranges

Specification

| | |
|---------------------------|---------------------------------|
| MATERIAL | Brass nickel plated (CuZn39Pb3) |
| SEALING RING | Fluorine rubber FKM (Viton) |
| O-RING | Flourgummi FKM (Viton) |
| INGRESS PROTECTION | IP66 / IP67 / IP69 |
| TEMPERATURE RANGE | -40°C...+200°C |
| TEST STANDARD | EN 62444 |

Variants

| ARTICLE NO. | CONNECTION THREAD | FOR CABLE Ø MM | L MM | D1 MM | D2 MM | H MM | SW1 MM | SW2 MM | PCS/PACK |
|--------------|-------------------|----------------|------|-------|-------|------|--------|--------|----------|
| K155-1012-00 | M12x1,5 | 3 - 8 | 6,5 | 8 | 5 | 25,5 | 16 | 16 | 100 |
| K155-1016-00 | M16x1,5 | 5 - 10,5 | 7 | 10,5 | 7,5 | 31,5 | 20 | 20 | 100 |
| K155-1020-00 | M20x1,5 | 8 - 15 | 8 | 12 | 10,5 | 33 | 25 | 25 | 50 |
| K155-1025-00 | M25x1,5 | 14 - 20,5 | 8 | 20,5 | 15,5 | 35,5 | 32 | 32 | 50 |
| K155-1032-00 | M32x1,5 | 18 - 25,5 | 9 | 25,5 | 20,5 | 9 | 36 | 36 | 25 |
| K155-1040-00 | M40x1,5 | 24 - 33 | 9 | 33 | 29 | 43 | 45 | 45 | 10 |
| K155-1050-00 | M50x1,5 | 32 - 42 | 10 | 42 | 37,5 | 47,5 | 55 | 55 | 5 |
| K155-1063-00 | M63x1,5 | 40 - 53 | 10 | 53 | 46 | 53 | 70 | 70 | 5 |