



Cable gland Brass IP68 Blueglobe HT Metric

For high temperature ranges

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
SEALING RING	Silikon HT
O-RING	Silicone
INGRESS PROTECTION	IP68 - 15 bar, IP69K
TEMPERATURE RANGE	-55°C...+200°C
COLOUR	Brass nickel plated
TEST STANDARD	EN 62444

Variants

ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	CABLE Ø MM WITHOUT INLET	CABLE Ø MM WITH INLET	L MM	H MM	SWI MM	E1 MM	PCS/PACK
bg212msHT	M12x1,5	2,0 - 8,0	5,0 - 8,0	2,0 - 5,0	5	26	17	18,9	50
bg216msHT	M16x1,5	4,0 - 11,0	7,0 - 11,0	4,0 - 7,0	6	31	20	22,2	50
bg220msHT	M20x1,5	5,0 - 14,0	9,0 - 14,0	5,0 - 9,0	6,5	36	24	26,5	50
bg225msHT	M25x1,5	11,0 - 20,0	16,0 - 20,0	11,0 - 16,0	7,5	37,5	30	33	50
bg232msHT	M32x1,5	15,0 - 25,0	20,0 - 25,0	15,0 - 20,0	8	40	36	39,5	25
bg240msHT	M40x1,5	20,0 - 32,0	26,0 - 32,0	20,0 - 26,0	8	43	45	48	10
bg250msHT	M50x1,5	31,0 - 42,0	35,0 - 42,0	31,0 - 35,0	10	49	57	61	5
bg263msHT	M63x1,5	41,0 - 54,0	46,0 - 54,0	41,0 - 46,0	10	50	68	72	5
bg812msHT	M12x1,5	2,0 - 8,0	5,0 - 8,0	2,0 - 5,0	15	36	17	18,9	50
bg816msHT	M16x1,5	4,0 - 11,0	7,0 - 11,0	4,0 - 7,0	15	40	20	22,2	50
bg820msHT	M20x1,5	5,0 - 14,0	9,0 - 14,0	5,0 - 9,0	15	44,5	24	26,5	50
bg825msHT	M25x1,5	11,0 - 20,0	16,0 - 20,0	11,0 - 16,0	15	45	30	33	50
bg832msHT	M32x1,5	15,0 - 25,0	20,0 - 25,0	15,0 - 20,0	15	47	36	39,5	25
bg840msHT	M40x1,5	20,0 - 32,0	26,0 - 32,0	20,0 - 26,0	15	50	45	48	10
bg850msHT	M50x1,5	31,0 - 42,0	35,0 - 42,0	31,0 - 35,0	15	54	57	61	5
bg863msHT	M63x1,5	41,0 - 54,0	46,0 - 54,0	41,0 - 46,0	15	55	68	72	5