



Cable Gland Brass IP68 Reducing Sealing ring Metric

- Reducing sealing ring for small cablediameter. E-1475701 with sealing ring in one-piece.
- Integrated anchorage
- Protection against twisting
- Easy-to-install

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
LAMELLAR INSERT	Polyamide PA6 V-2
SEALING RING / INNER PART	Evoprene TPE
SEALING RING / OUTER PART	Polychloroprene-Nitrile rubber CR/NBR
O-RING	Nitrile Rubber NBR
INGRESS PROTECTION	IP68 - 5 bar
TEMPERATURE RANGE	-20°C...+100°C (dynamisk) -40°C (static, short term)
COLOUR	Brass nickel plated
TEST STANDARD	EN 62444 / UL514B
VDE LICENCE	40020901
UL / CSA-FILE	E140310
SEV LICENCE	02.1465
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1475701	M12x1,5	2 - 5	5	25	14	15.5	100
1475702	M16x1,5	3 - 9	5	30	17	19	100
1475703	M20x1,5	5 - 13	6	33,5	22	24	100
1475704	M25x1,5	8 - 16	7	36,5	27	30	50
1475705	M32x1,5	12 - 20	8	38	34	36	25
1475706	M40x1,5	16 - 27	8	41	43	46	10
1475707	M50x1,5	21 - 35	9	49,5	55	60	5
1475708	M63x1,5	27 - 48	10	52,5	65	70	5