



Cable Gland Brass IP68 UNI Dicht 50mm long thread Metric

Specification

| | |
|---------------------------|---------------------------------|
| MATERIAL | Brass nickel plated (CuZn39Pb3) |
| SEALING RING | TPE |
| O-RING | NBR |
| INGRESS PROTECTION | IP68 up to 10 bar |
| TEMPERATURE RANGE | -40°C...+130°C |
| COLOUR | Brass nickel plated |
| HALOGEN-FREE | Yes |

Variants

| E-NUMBER | ARTICLE NO. | CONNECTION THREAD | FOR CABLE Ø MM | L MM | H MM | SW1 MM | SW2 MM | E1 MM | E2 MM | PCS/PACK |
|----------|---------------|-------------------|----------------|------|------|--------|--------|-------|-------|----------|
| - | 22052D7/50lg | M20x1,5 | 4,0 - 6,5 | 50 | 71 | 22 | 22 | 24.4 | 24.4 | 10 |
| - | 22052D8/50lg | M20x1,5 | 5,0 - 8,0 | 50 | 71 | 22 | 22 | 24.4 | 24.4 | 10 |
| - | 22052D9/50lg | M20x1,5 | 6,5 - 9,5 | 50 | 71 | 22 | 22 | 24.4 | 24.4 | 10 |
| - | 22052D11/50lg | M20x1,5 | 7,0 - 10,5 | 50 | 71 | 22 | 22 | 24.4 | 24.4 | 10 |
| - | 22052D13/50lg | M20x1,5 | 9,0 - 13,0 | 50 | 71 | 22 | 22 | 24.4 | 24.4 | 10 |
| - | 22553D7/50lg | M25x1,5 | 4,0 - 6,5 | 50 | 71 | 28 | 24 | 31.2 | 26.7 | 10 |
| - | 22553D8/50lg | M25x1,5 | 5,0 - 8,0 | 50 | 71 | 28 | 24 | 31.2 | 26.7 | 10 |
| - | 22553D9/50lg | M25x1,5 | 6,5 - 9,5 | 50 | 71 | 28 | 24 | 31.2 | 26.7 | 10 |
| - | 22553D11/50lg | M25x1,5 | 7,0 - 10,5 | 50 | 71 | 28 | 24 | 31.2 | 26.7 | 10 |
| - | 22553D13/50lg | M25x1,5 | 9,0 - 13,0 | 50 | 71 | 28 | 24 | 31.2 | 26.7 | 10 |
| - | 22553D16/50lg | M25x1,5 | 11,5 - 15,5 | 50 | 71 | 28 | 24 | 31.2 | 26.7 | 10 |
| - | 23254D11/50lg | M32x1,5 | 7,0 - 10,5 | 50 | 76 | 35 | 30 | 38.5 | 33.5 | 5 |
| - | 23254D13/50lg | M32x1,5 | 9,0 - 13,0 | 50 | 76 | 35 | 30 | 38.5 | 33.5 | 5 |
| - | 23254D16/50lg | M32x1,5 | 11,5 - 15,5 | 50 | 76 | 35 | 30 | 38.5 | 33.5 | 5 |
| - | 23254D18/50lg | M32x1,5 | 14,0 - 18,0 | 50 | 76 | 35 | 30 | 38.5 | 33.5 | 5 |
| - | 23254D20/50lg | M32x1,5 | 17,0 - 20,5 | 50 | 76 | 35 | 30 | 38.5 | 33.5 | 5 |
| - | 24055D16/50lg | M40x1,5 | 11,5 - 15,5 | 50 | 79 | 43 | 40 | 47.3 | 43.5 | 5 |
| - | 24055D18/50lg | M40x1,5 | 14,0 - 18,0 | 50 | 79 | 43 | 40 | 47.3 | 43.5 | 5 |
| - | 24055D20/50lg | M40x1,5 | 17,0 - 20,5 | 50 | 79 | 43 | 40 | 47.3 | 43.5 | 5 |
| - | 24055D25/50lg | M40x1,5 | 20,0 - 25,0 | 50 | 79 | 43 | 40 | 47.3 | 43.5 | 5 |
| - | 24055D28/50lg | M40x1,5 | 24,0 - 28,0 | 50 | 79 | 43 | 40 | 47.3 | 43.5 | 5 |