



Cable Gland Brass "WADI-one" IP66/IP68/IP69

- large-area sealing protects the cable
- increased anchorage with high retention
- wide sealing and clamping range
- the inner sealing ring can be removed easily for larger cables
- material of the sealing insert fulfills UL 94 HB
- high UV, ozone and weather resistance

Specification

| | |
|---------------------------|-------------------------------------|
| MATERIAL | Brass nickel plated (CuZn39Pb3) |
| SEALING RING | TPE TPS |
| O-RING | NBR |
| INGRESS PROTECTION | IP66, IP68 - 10 bar (30 min.), IP69 |
| TEMPERATURE RANGE | -40°C...+100°C |
| COLOUR | Brass nickel plated |
| TEST STANDARD | EN 62444 |

Variants

| E-NUMBER | CONNECTION THREAD | FOR CABLE Ø MM | L MM | D1 MM | D2 MM | H MM | SW1 MM | SW2 MM | PCS/PACK |
|----------|-------------------|----------------|------|-------|-------|------|--------|--------|----------|
| 1476961 | M12x1,5 | 3 - 8 | 6.5 | 8 | 5 | 25.5 | 16 | 16 | 100 |
| 1476962 | M16x1,5 | 5 - 10,5 | 7 | 10.5 | 7.5 | 31.5 | 20 | 20 | 100 |
| 1476963 | M20x1,5 | 8 - 15 | 8 | 15 | 10.5 | 33 | 25 | 25 | 50 |
| 1476964 | M25x1,5 | 12,5 - 20,5 | 8 | 20.5 | 15.5 | 35.5 | 32 | 32 | 50 |
| 1476965 | M32x1,5 | 17 - 25,5 | 9 | 25.5 | 20.5 | 40.5 | 36 | 36 | 25 |
| 1476966 | M40x1,5 | 24 - 33 | 9 | 33 | 29 | 43 | 45 | 45 | 10 |
| 1476967 | M50x1,5 | 31 - 42 | 10 | 42 | 37.5 | 47.7 | 55 | 55 | 5 |
| 1476968 | M63x1,5 | 40 - 53 | 10 | 53 | 46 | 53 | 70 | 70 | 5 |