



## Cable Gland Lead-Free Brass IP68 Long thread Metric

### Lead-Free

- Long connection thread
- Integrated anchorage
- Protection against twisting
- Easy-to-install
- Lead-Free

\* IP69K tested for M12-M25, M50 & M63

## Specification

<b>MATERIAL</b>	Brass nickel plated (CuZn21Si3P)
<b>LAMELLAR INSERT</b>	Polyamide PA6 V-2
<b>SEALING RING</b>	Polychloroprene-Nitrile rubber CR/NBR
<b>O-RING</b>	Nitrile Rubber NBR
<b>INGRESS PROTECTION</b>	IP68 - 5 bar, IP69K*
<b>TEMPERATURE RANGE</b>	-20°C...+100°C (dynamisk) -40°C (static, short term)
<b>COLOUR</b>	Brass nickel plated
<b>TEST STANDARD</b>	EN 62444 / UL514B
<b>VDE LICENCE</b>	40020901
<b>UL / CSA-FILE</b>	E140310
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1473211	50.612Y-L	M12x1,5	3 - 6	10	30	14	15.5	100
1473212	50.616Y-L	M16x1,5	5 - 9	10	35	17	19	100
1473213	50.620Y-L	M20x1,5	9 - 13	10	37,5	22	24	100
1473214	50.625Y-L	M25x1,5	11 - 16	11	40,5	27	30	50
1473215	50.632Y-L	M32x1,5	14 - 20	13	43	34	36	25
1473216	50.640Y-L	M40x1,5	19 - 27	13	46	43	46	10
1473217	50.650Y-L	M50x1,5	24 - 35	14	54,5	55	60	5
1473218	50.663Y-L	M63x1,5	32 - 42	14	56,5	65	70	5
1473219	50.663Y1-L	M63x1,5	38 - 48	14	56,5	65	70	5