



Cable Gland Lead-Free Brass IP68 Metric

Lead-Free

- Integrated anchorage
- Protection against twisting
- Easy-to-install
- Lead-Free

* IP69K tested for M12-M25, M50 & M63

Specification

MATERIAL	Brass nickel plated (CuZn21Si3P)
LAMELLAR INSERT	Polyamide PA6 V-2
SEALING RING	Polychloroprene-Nitrile rubber CR/NBR
O-RING	Nitrile Rubber NBR
INGRESS PROTECTION	IP68 - 5 bar, IP69K*
TEMPERATURE RANGE	-20°C...+100°C (dynamisk) -40°C (static, short term)
COLOUR	Brass nickel plated
TEST STANDARD	EN 62444 / UL514B
VDE LICENCE	40020901
UL / CSA-FILE	E140310
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1473201	50.612Y	M12x1,5	3 - 6	5	25	14	15,5	100
1473202	50.616Y	M16x1,5	5 - 9	5	30	17	19	100
1473203	50.620Y	M20x1,5	9 - 13	6	33,5	22	24	100
1473204	50.625Y	M25x1,5	11 - 16	7	36,5	27	30	50
1473205	50.632Y	M32x1,5	14 - 20	8	38	34	36	25
1473206	50.640Y	M40x1,5	19 - 27	8	41	43	46	10
1473207	50.650Y	M50x1,5	24 - 35	9	49,5	55	60	5
1473208	50.663Y	M63x1,5	32 - 42	10	52,5	65	70	5
1473209	50.663Y1	M63x1,5	38 - 48	10	52,5	65	70	5