



## Screw plug Brass IP66/IP68 with O-ring Metric

### Specification

<b>MATERIAL</b>	Brass nickel plated (CuZn39Pb3)
<b>O-RING</b>	Nitrile Rubber NBR
<b>INGRESS PROTECTION</b>	IP66, IP68 - 5 bar, type 4X
<b>TEMPERATURE RANGE</b>	-40°C...+100°C
<b>COLOUR</b>	Brass nickel plated
<b>TEST STANDARD</b>	UL 514A, 25 / UL 50, 35.2 / UL 746C, 14
<b>UL / CSA-FILE</b>	E140310
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	CONNECTION THREAD	L MM	L1 MM	DA MM	DI MM	H MM	PCS/PACK
1476561	M12x1,5	5	5	16	8,5	8	100
1476562	M16x1,5	6	6	20	12,5	9	100
1476563	M20x1,5	6,5	6	24	15	9,5	100
1476564	M25x1,5	7	6,5	28	19	11	100
1476565	M32x1,5	8	7,5	35	26	12	50
1476566	M40x1,5	8	7,5	45	34	12	50
1476567	M50x1,5	9	8,5	55	44	15	25
1476568	M63x1,5	10	9,5	68	57	16	10