



Cable Gland IP68 EMC NPT

- For cables with shielding
- Integrated anchorage
- Reducing sealing ring (bipartite)
- Protection against twisting by the construction of the lamellar insert.

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
LAMELLAR INSERT	Polyamide PA6 V-2
SEALING RING / OUTER PART	Polychloroprene-Nitrile rubber CR/NBR
O-RING	Nitrile Rubber NBR
TEMPERATURE RANGE	-20°C...+100°C (dynamisk) -40°C (static, short term)
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
50.114/EMV/R	NPT 1/4"	3 - 9	8	33	17	19	50
50.138/EMV/R	NPT 1/2"	3 - 9	8	33	20	22	50
50.112/EMV/R	NPT 1/2"	5 - 13	10	37.5	24	26.7	50
50.134/EMV/R	NPT 3/4"	8 - 16	11	40.5	30	33.5	50
50.110/EMV/R	NPT 1"	12 - 20	14	44	40	44	25
50.1114/EMV/R	NPT 1 1/4"	16 - 27	14	47	50	54	10
50.1112/EMV/R	NPT 1 1/2"	21 - 35	15	55.5	55	59	5
50.1200/EMV/R	NPT 2"	27 - 48	15	57.5	65	70	5