



Cable Gland Brass IP54 increased anchorage PG

E-14 607 51 with one-part sealing ring 5-7mm.

- Increased anchorage
- Multiple perforations for wide sealing range

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
SEALING RING	Perbunan NBR
INGRESS PROTECTION	IP54
TEMPERATURE RANGE	-20°C...+80°C
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW1 MM	SW2 MM	E1 MM	E2 MM	PCS/PACK
1460751	PG7/12,5	5 - 7	5	27,3	16	14	17.5	15.5	50
1460750	PG9/15,2	5 - 10	6	28,7	19	17	20.3	19.9	50
1460752	PG11/18,6	7,5 - 12	6	32,2	22	20	24	22.2	50
1460754	PG13,5/20,4	7,5 - 13	6.5	33,7	24	22	26.4	24.4	50
1460756	PG16/22,5	7,5 - 15	6.5	34,8	27	24	30	26.7	50
1460758	PG21/28,3	10 - 20	7	38,7	34	30	37.8	33.5	25
1460760	PG29/37,0	18 - 27	8	42,3	42	40	46.5	43.5	25
1460762	PG36/47,0	24 - 32	9	49	52	50	56	54	10
1460763	PG42/54,0	30 - 42	10	52,7	59	57	65	61	5
1460764	PG48/59,3	36 - 46	10	54,7	64	64	69.8	69	5