



Cable Gland Brass IP55 multiple perforations PG

- Multiple perforations for wide sealing range

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
SEALING RING	SBR/NBR
WASHER	Steel, zinc-plated
INGRESS PROTECTION	IP55
TEMPERATURE RANGE	-30°C...+100°C
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW1 MM	SW2 MM	E1 MM	PCS/PACK
1460565	PG9/15,2	4 - 10	6	22,5	17	15	19	100
1460568	PG11/18,6	6 - 12	6	23,5	20	18	22	50
1460570	PG13,5/20,4	6 - 13	6,5	25,5	22	20	24	50
1460572	PG16/22,5	6 - 16	6,5	26,5	24	22	26	50
1460578	PG21/28,3	9 - 20	7	29,5	30	28	33	50
1460587	PG29/37,0	17 - 28	8	33	40	37	44	25
1460597	PG36/47,0	23 - 34	9	39	50	47	54	10
1460598	PG42/54,0	29 - 40	10	44,5	57	54	60	5
1460599	PG48/59,3	35 - 47	10	46	64	60	69	5