



## Cable Gland Brass IP55 PG

### Specification

<b>MATERIAL</b>	Brass nickel plated (CuZn39Pb3)
<b>SEALING RING</b>	SBR/NBR
<b>WASHER</b>	Steel, zinc-plated
<b>INGRESS PROTECTION</b>	IP55
<b>TEMPERATURE RANGE</b>	-30°C...+100°C
<b>COLOUR</b>	Brass nickel plated
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW1 MM	SW2 MM	E1 MM	PCS/PACK
6307	PG7/12,5	5 - 7	5	21	14	13	15.5	100
6309	PG9/15,2	6 - 8	6	22,5	17	15	19	100
6311	PG11/18,6	8 - 10	6	23,5	20	18	22	50
6313	PG13,5/20,4	10 - 12	6.5	25,5	22	20	24	50
6316	PG16/22,5	12 - 14	6.5	27	24	22	26	50
6321	PG21/28,3	15 - 17	7	29,5	30	28	33	50
6329	PG29/37,0	24 - 26	8	33	40	37	44	25
6336	PG36/47,0	31 - 33	9	39	50	47	54	10
6342	PG42/54,0	38 - 40,5	10	44,5	57	54	60	5
6348	PG48/59,3	45 - 47	10	46	64	60	69	5