



Cable Gland Brass IP68 PG

- Integrated anchorage
- Protection against twisting
- Easy-to-install

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
LAMELLAR INSERT	Polyamide PA6 V-2
SEALING RING	Polychloroprene-Nitrile rubber CR/NBR
O-RING	Nitrile Rubber NBR
INGRESS PROTECTION	IP68 - 5 bar
TEMPERATURE RANGE	-20°C....+100°C (dynamisk) -40°C (static, short term)
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1460402	PG7/12,5	3 - 6,5	5	24	14	15.5	100
1460405	PG9/15,2	4 - 8	6	29	17	19	100
1460408	PG11/18,6	5 - 10	6	29,5	20	22	50
1460410	PG13,5/20,4	6 - 12	6,5	31,5	22	24	50
1460412	PG16/22,5	10 - 14	6,5	31,5	24	26.7	50
1460414	PG21/28,3	13 - 18	7	34	30	33.5	50
1460417	PG29/37,0	18 - 25	8	39	40	44	25
1460419	PG36/47,0	24 - 32	9	45	50	54	10
1460421	PG42/54,0	30 - 38	10	49	57	61	5
1460423	PG48/59,3	34 - 44	10	52	64	69	5