



Cable Gland Brass IP68 UNI Dicht Long thread PG

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
SEALING RING	TPE
O-RING	NBR
INGRESS PROTECTION	IP68 up to 10 bar
TEMPERATURE RANGE	-40°C...+130°C
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW1 MM	SW2 MM	E1 MM	E2 MM	PCS/PACK
N9387003	180D7	PG9/15,2	4,0 - 6,5	15	35	17	17	18,9	18,9	50
N9387004	180D8	PG9/15,2	5,0 - 8,0	15	35	17	17	18,9	18,9	50
N9387005	180D9	PG9/15,2	6,5 - 9,0	15	35	17	17	18,9	18,9	50
N9387008	181D7	PG11/18,6	4,0 - 6,5	15	35	20	20	22,2	22,2	50
N9387009	181D8	PG11/18,6	5,0 - 8,0	15	35	20	20	22,2	22,2	50
N9387010	181D9	PG11/18,6	6,5 - 9,5	15	35	20	20	22,2	22,2	50
N9387011	181D11	PG11/18,6	7,0 - 10,5	15	35	20	20	22,2	22,2	50
N9387012	182D7	PG13,5/20,4	4,0 - 6,5	15	36	22	22	24,4	24,4	50
N9387013	182D8	PG13,5/20,4	5,0 - 8,0	15	36	22	22	24,4	24,4	50
N9387014	182D9	PG13,5/20,4	6,5 - 9,5	15	36	22	22	24,4	24,4	50
N9387015	182D11	PG13,5/20,4	7,0 - 10,5	15	36	22	22	24,4	24,4	50
N9387016	182D13	PG13,5/20,4	9,0 - 13,0	15	36	22	22	24,4	24,4	50
N9387020	183D7	PG16/22,5	4,0 - 6,5	15	36	24	24	26,7	26,7	50
N9387021	183D8	PG16/22,5	5,0 - 8,0	15	36	24	24	26,7	26,7	50
N9387022	183D9	PG16/22,5	6,5 - 9,5	15	36	24	24	26,7	26,7	50
N9387023	183D11	PG16/22,5	7,0 - 10,5	15	36	24	24	26,7	26,7	50
N9387024	183D13	PG16/22,5	9,0 - 13,0	15	36	24	24	26,7	26,7	50
N9387025	183D16	PG16/22,5	11,5 - 15,5	15	36	24	24	26,7	26,7	50
N9387030	184D11	PG21/28,3	7,0 - 10,5	15	40	30	30	33,5	33,5	25
N9387031	184D13	PG21/28,3	9,0 - 13,0	15	40	30	30	33,5	33,5	25
N9387032	184D16	PG21/28,3	11,5 - 15,5	15	40	30	30	33,5	33,5	25
N9387033	184D18	PG21/28,3	14,0 - 18,0	15	40	30	30	33,5	33,5	25
N9387034	184D20	PG21/28,3	17,0 - 20,5	15	40	30	30	33,5	33,5	25
N9387035	185D16	PG29/37,0	11,5 - 15,5	15	42	40	40	43,5	43,5	10
N9387036	185D18	PG29/37,0	14,0 - 18,0	15	42	40	40	43,5	43,5	10
N9387037	185D20	PG29/37,0	17,0 - 20,5	15	42	40	40	43,5	43,5	10
N9387038	185D25	PG29/37,0	20,0 - 25,0	15	42	40	40	43,5	43,5	10
N9387039	185D28	PG29/37,0	24,0 - 28,0	15	42	40	40	43,5	43,5	10
N9387040	186D32	PG36/47,0	27,0 - 32,0	15	43	50	50	54	54	10
N9387041	186D34	PG36/47,0	29,0 - 34,0	15	43	50	50	54	54	10
N9387042	186D36	PG36/47,0	32,0 - 36,0	15	43	50	50	54	54	10
N9387043	187D40	PG42/54,0	36,0 - 40,0	15	45	57	57	61	61	5
N9387044	188D44	PG48/59,3	39,0 - 44,0	15	45	64	64	69	69	5