



Cable Gland IP68 EMC blueglobe TRI Metric

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
SEALING RING	TPE
O-RING	HNBR
CONTACT SPRING	Stainless steel 1.4310
INGRESS PROTECTION	IP68 - 15 bar, IP69K
TEMPERATURE RANGE	-40°C...+130°C
COLOUR	Brass nickel plated
TEST STANDARD	EN 62444
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	CABLE Ø MM WITHOUT INLET	CABLE Ø MM WITH INLET	SCREEN Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1471920	BG212MSTRI	M12x1,5	5 - 8	5,0 - 8,0	-	3 - 5	5	26	17	18,9	50
1471921	BG216MSTRI	M16x1,5	7 - 11	7,0 - 11,0	-	5 - 9	6	31	20	22,2	50
1471922	BG220MSTRI	M20x1,5	9 - 14	9,0 - 14,0	-	7 - 12	6,5	35,5	24	26,5	50
1471923	BG225MSTRI	M25x1,5	11 - 20	16,0 - 20,0	11,0 - 16,0	10 - 16	7,5	37,5	30	33	50
1471924	BG232MSTRI	M32x1,5	15 - 25	20,0 - 25,0	15,0 - 20,0	13 - 20	8	40	36	39,5	25
1471925	BG240MSTRI	M40x1,5	20 - 32	26,0 - 32,0	20,0 - 26,0	20 - 28	15	50	45	48	10
1471926	BG250MSTRI	M50x1,5	31 - 42	35,0 - 42,0	31,0 - 35,0	28 - 37	15	54	57	61	5
1471927	BG263MSTRI	M63x1,5	41 - 54	46,0 - 54,0	41,0 - 46,0	37 - 46	20	60	68	72	5
1471928	BG275MSTRI	M75x1,5	54 - 65	58,0 - 65,0	54,0 - 58,0	46 - 58	20	67	81	87	5
1471929	BG285MSTRI	M85x2,0	65 - 77	70,0 - 77,0	65,0 - 70,0	58 - 65	20	69	95	102	1