



## Cable Gland IP68 EMC long thread Metric

- Long connection thread
- For cables with shielding
- Integrated anchorage
- Protection against twisting by the construction of the lamellar insert.

### Specification

<b>MATERIAL</b>	Brass nickel plated (CuZn39Pb3)
<b>LAMELLAR INSERT</b>	Polyamide PA6 V-2
<b>SEALING RING</b>	Polychloroprene-Nitrile rubber CR/NBR
<b>O-RING</b>	Nitrile Rubber NBR
<b>INGRESS PROTECTION</b>	IP68 - 5 bar
<b>TEMPERATURE RANGE</b>	-20°C...+100°C (dynamisk) -40°C (static, short term)
<b>COLOUR</b>	Brass nickel plated
<b>TEST STANDARD</b>	EN 62444 / UL514B
<b>VDE LICENCE</b>	40020901
<b>UL / CSA-FILE</b>	E140310
<b>SEV LICENCE</b>	02.1466
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1476031	M12x1,5	3 - 6	10	30	14	15,5	100
1476032	M16x1,5	5 - 9	10	35	17	19	100
1476033	M20x1,5	9 - 13	10	37,5	22	24	100
1476034	M25x1,5	11 - 16	11	40,5	27	30	50
1476035	M32x1,5	14 - 20	13	43	34	36	25
1476036	M40x1,5	19 - 27	13	46	43	46	10
1476037	M50x1,5	24 - 35	14	54,5	55	60	5
1476038	M63x1,5	32 - 42	14	56,5	65	70	5