



Cable Gland IP68 EMC Metric

- For cables with shielding
- Integrated anchorage
- Protection against twisting by the construction of the lamellar insert.

* IP69K tested for M12-M25, M50 & M63

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
LAMELLAR INSERT	Polyamide PA6 V-2
SEALING RING	Polychloroprene-Nitrile rubber CR/NBR
O-RING	Nitrile Rubber NBR
INGRESS PROTECTION	IP68 - 5 bar, IP69K*
TEMPERATURE RANGE	-20°C...+100°C (dynamisk) -40°C (static, short term)
COLOUR	Brass nickel plated
TEST STANDARD	EN 62444 / UL514B
VDE LICENCE	40020901
UL / CSA-FILE	E140310
SEV LICENCE	02.1466
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1476021	M12x1,5	3 - 6	5	25	14	15,5	100
1476022	M16x1,5	5 - 9	5	30	17	19	100
1476023	M20x1,5	9 - 13	6	33,5	22	24	100
1476024	M25x1,5	11 - 16	7	36,5	27	30	50
1476025	M32x1,5	14 - 20	8	38	34	36	25
1476026	M40x1,5	19 - 27	8	41	43	46	10
1476027	M50x1,5	24 - 35	9	49,5	55	60	5
1476028	M63x1,5	32 - 42	10	52,5	65	70	5