



Cable Gland IP68 EMC PG

- For cables with shielding
- Integrated anchorage
- Protection against twisting by the construction of the lamellar insert.

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
LAMELLAR INSERT	Polyamide PA6 V-2
SEALING RING	Polychloroprene-Nitrile rubber CR/NBR
O-RING	Nitrile Rubber NBR
INGRESS PROTECTION	IP68 - 5 bar
TEMPERATURE RANGE	-20°C....+100°C (dynamisk) -40°C (static, short term)
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	DI MM	H MM	SWI MM	E1 MM	PCS/PACK
1460800	PG7/12,5	3 - 6,5	5	6,5	24	14	15,5	100
1460801	PG9/15,2	4 - 8	6	8	29	17	19	100
1460802	PG11/18,6	5 - 10	6	10	29,5	20	22	50
1460803	PG13,5/20,4	6 - 12	6,5	12	31,5	22	24	50
1460804	PG16/22,5	10 - 14	6,5	14	31,5	24	26,7	50
1460805	PG21/28,3	13 - 18	7	18	34	30	33,5	50
1460806	PG29/37,0	18 - 25	8	25	39	40	44	25
1460807	PG36/47,0	24 - 32	9	32	45	50	54	10
1460808	PG42/54,0	30 - 38	10	38	49	57	61	5
1460809	PG48/59,3	34 - 44	10	44	52	64	69	5