



Cable Gland IP68 EMC with Contact spring Metric

- For cables with shielding
- Integrated anchorage
- Quick and easy EMC connection of the cable shield via the contacting spring
- Protection against twisting by the construction of the lamellar insert

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
LAMELLAR INSERT	Polyamide PA6 V-2
SEALING RING	Polychloroprene-Nitrile rubber CR/NBR
O-RING	Nitrile Rubber NBR
CONTACT SPRING	Stainless steel
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-20°C...+100°C (dynamisk) -40°C (static, short term)
COLOUR	Brass nickel plated
TEST STANDARD	UL 514B
UL / CSA-FILE	E140310
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	SCREEN Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1475922	M16x1,5	5 - 9	2 - 8	5	30	17	19	100
1475923	M20x1,5	9 - 13	3 - 11	6	33,5	22	24	100
1475924	M25x1,5	11 - 16	8 - 14	7	36,5	27	30	50
1475925	M32x1,5	14 - 20	10 - 19	8	38	34	36	25
1475926	M40x1,5	19 - 27	15 - 25	8	41	43	46	10
1475927	M50x1,5	24 - 35	22 - 33	9	49,5	55	60	5
1475928	M63x1,5	32 - 42	31 - 40	10	52,5	65	70	5