



Blanking plug IP66 Ex e Metric

Protective closure for uninstalled "PERFECT" Ex-cable glands

- E-14 675 48-56
- E-14 675 59-67
- E-14 675 70-78
- E-14 675 81-89.

Specification

MATERIAL	Polyamide PA6
INGRESS PROTECTION	IP66
TEMPERATURE RANGE	-55°C...+70°C
COLOUR	Red
TEST STANDARD	EN 60079-0:2012, IEC 60079-0:2011, EN 60079-7:2007, IEC 60079-7:2006, EN 60079-31:2009, IEC 60079-31:2008
CATEGORY / ZONE	2 G (1,2) 2 D (21,22)
EQUIPMENT GROUP	II
TYPE OF PROTECTION	Ex e IIC Gb Ex tb IIIC Db
EU-TYPE CERTIFICATE	PTB 99 ATEX 3101 X (M12 and M16) / PTB 99 ATEX 3128 X (M20 to M63)
IECEX CERTIFICATE	IECEX PTB 05.0004X, IECEX PTB 14.0027X
HALOGEN-FREE	Yes

Variants

E-NUMBER	FOR SIZE	Ø D1 MM	D MM	H MM	PCS/PACK
1465717	M12x1,5	5	7	30.3	20
1467510	M16x1,5	6	8	33	20
1467511	M20x1,5	7	12	34.5	20
1467512	M25x1,5	10	16	36	20
1467513	M32x1,5	13	20	40	20
1467514	M40x1,5	19	24	42	10