



## Cable Gland Brass LevelEx Ex-d/Ex-e NPT

### Ex-d/Ex-e for non armoured cable

The cable gland LevelEx® provides a single pull resistant seal on the outer sheath of any cable. It maintains Flameproof “Ex-d” and Increased Safety “Ex-e” methods of explosion protection, IP 66 + IP 68 (10 bar, 1 hour).

- Compact design
- IP66 and IP68 (10 bar, 1hour)
- Quick and easy installation

## Specification

<b>MATERIAL</b>	Brass nickel plated (CuZn39Pb3)
<b>SEALING RING</b>	Silicone
<b>INGRESS PROTECTION</b>	IP66 + IP68 (10 bar, 1h)
<b>TEMPERATURE RANGE</b>	-60°C...+130°C
<b>STANDARDS</b>	Compliance: EN60079-0:2012 + A11:2013, EN 60079-1:2014 Standard: EN 60079-7:2015, EN 60079-31:2014 IEC 60079-0:2017, IEC 60079-1:2014, IEC 60079-7:2015, IEC 60079-31:2013
<b>CERTIFICATIONS</b>	Designation gas: II 2G Ex db eb IIC Gb Designation dust: II 2D Ex ta IIIC Da IP 66/68 Certificate No. ATEX: PTB 18 ATEX 1001X xx CE 0102 IECEX: IECEX PTB 18.0001X EAC: RU C-DE.AA71.B.00390

## Variants

ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW MM	E MM	PCS/PACK
Lex3038msHTS	NPT3/8"	7,0 - 11,0	16	48	20	22	10
Lex3034msHTS	NPT3/4"	12,5 - 20,0	20,5	60,5	30	32,5	10
Lex3012msHTS	NPT1/2"	8,0 - 14,0	20	57	24	26	10
Lex3100msHTS	NPT1"	18,5 - 26,0	25	68	36	39	10
Lex3114msHTS	NPT1 1/4"	26,0 - 34,0	26	72,5	46	50	5
Lex3200msHTS	NPT2"	33,0 - 45,0	27	78	68	72	5
Lex3212msHTS	NPT2 1/2"	44,0 - 56,0	40	95	81	87	1