



Cable Gland Polyamide IP66/68 Ex e long thread Metric

Ex-e for non armoured cable

Specification

MATERIAL	Polyamide
SEALING RING	EPDM
INGRESS PROTECTION	IP66, IP68 - 5 bar (30 min.)
TEMPERATURE RANGE	-40°C....+75°C (M12 +15°C....+65°C)
COLOUR	Black RAL 9005
CATEGORY / ZONE	2 G (1,2) 2 D (21,22)
EQUIPMENT GROUP	II
TYPE OF PROTECTION	Ex eb, Ex tb
CERTIFICATIONS	IECEX, ATEX

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW MM	E MM	PCS/PACK
1467685	ESKE/1-L-E 12	M12x1,5	3 - 6	15	40	16	18	50
1467686	ESKE/1-L-E 16	M16x1,5	4,5 - 9	15	43	20	22	50
1467687	ESKE/1-L-E 20	M20x1,5	7 - 13	15	48	24	27	50
1467688	ESKE/1-L-E 25	M25x1,5	10 - 17	15	51	29	32	50
1467689	ESKE/1-L-E 32	M32x1,5	13 - 21	15	53	36	40	25
1467690	ESKE/1-L-E 40	M40x1,5	17 - 28	18	71	46	51	10
1467691	ESKE/1-L-E 50	M50x1,5	23 - 35	18	76	55	61	4
1467692	ESKE/1-L-E 63	M63x1,5	34 - 48	18	81	68	75	1