



Cable Gland Polyamide IP66/68 Ex e Metric

Ex-e for non armoured cable

Specification

MATERIAL	Polyamide
SEALING RING	EPDM
INGRESS PROTECTION	IP66, IP68 - 5 bar (30 min.)
TEMPERATURE RANGE	-40°C....+75°C (M12 +15°C....+65°C)
COLOUR	Black RAL 9005
CATEGORY / ZONE	2 G (1,2) 2 D (21,22)
EQUIPMENT GROUP	II
TYPE OF PROTECTION	Ex eb, Ex tb
CERTIFICATIONS	IECEX, ATEX

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW MM	E MM	PCS/PACK
1467592	ESKE/1-E 12	M12x1,5	3 - 6	9	37	16	18	50
1467593	ESKE/1-E 16	M16x1,5	4,5 - 9	9	37	20	22	50
1467594	ESKE/1-E 20	M20x1,5	7 - 13	10	45	24	27	50
1467595	ESKE/1-E 25	M25x1,5	10 - 17	10	47	29	32	50
1467596	ESKE/1-E 32	M32x1,5	13 - 21	12	51	36	40	25
1467597	ESKE/1-E 40	M40x1,5	17 - 28	12	65	46	51	10
1467598	ESKE/1-E 50	M50x1,5	23 - 35	14	72	55	61	4
1467599	ESKE/1-E 63	M63x1,5	34 - 48	15	78	68	75	1