



## Enlarger Brass IP66/68 Ex Metric - Metric

### Specification

<b>MATERIAL</b>	Brass nickel plated (CuZn39Pb3)
<b>O-RING</b>	Nitrile Rubber NBR
<b>INGRESS PROTECTION</b>	IP66, IP68 - 10 bar (30 min.)
<b>TEMPERATURE RANGE</b>	-40°C...+85°C
<b>COLOUR</b>	Brass nickel plated
<b>TEST STANDARD</b>	EN IEC 60079-0:2018, IEC 60079-0:2017, EN IEC 60079-7:2015+A1, IEC 60079-7:2015+A1, EN 60079-31:2014, IEC 60079-31:2013
<b>CATEGORY / ZONE</b>	2 G (1,2) 2 D (21,22)
<b>EQUIPMENT GROUP</b>	II
<b>TYPE OF PROTECTION</b>	Ex eb IIC Gb Ex tb IIIC Db
<b>EU-TYPE CERTIFICATE</b>	PTB 16 ATEX 1006
<b>IECEX CERTIFICATE</b>	IECEX PTB 16.0017

## Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	INTERNAL THREAD	L MM	DI MM	H MM	SWI MM	PCS/PACK
1467671	E102-11216-03-EX	M12x1,5	M16x1,5	5	8	16	18	100
1467672	E102-11620-03-EX	M16x1,5	M20x1,5	5	12	16,5	22	100
1467673	E102-12025-03-EX	M20x1,5	M25x1,5	6	15	18,5	27	50
1467674	E102-12532-03-EX	M25x1,5	M32x1,5	7	21	20,5	34	25
1467675	E102-13240-03-EX	M32x1,5	M40x1,5	8	26	23,5	42	25
1467676	E102-14050-03-EX	M40x1,5	M50x1,5	8	34	30	52	10
1467677	E102-15063-03-EX	M50x1,5	M63x1,5	9	44	32,5	65	10