



Screw plug Brass IP66/68 Ex Metric

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
O-RING	Nitrile Rubber NBR
INGRESS PROTECTION	IP66, IP68 - 10 bar (30 min.)
TEMPERATURE RANGE	-40°C...+85°C
COLOUR	Brass nickel plated
TEST STANDARD	EN IEC 60079-0:2018, IEC 60079-0:2017, EN IEC 60079-7:2015+A1, IEC 60079-7:2015+A1, EN 60079-31:2014, IEC 60079-31:2013
CATEGORY / ZONE	2 G (1,2) 2 D (21,22)
EQUIPMENT GROUP	II
TYPE OF PROTECTION	Ex eb IIC Gb Ex tb IIIC Db
EU-TYPE CERTIFICATE	PTB 16 ATEX 1006
IECEX CERTIFICATE	IECEX PTB 16.0017

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	L MM	DA MM	H MM	PCS/PACK
1467651	V102-1012-03-EX	M12x1,5	5	16	8	100
1467652	V102-1016-03-EX	M16x1,5	6	20	9	100
1467653	V102-1020-03-EX	M20x1,5	6,5	24	9,5	100
1467654	V102-1025-03-EX	M25x1,5	7	28	11	100
1467655	V102-1032-03-EX	M32x1,5	8	35	12	50
1467656	V102-1040-03-EX	M40x1,5	8	45	12	50
1467657	V102-1050-03-EX	M50x1,5	9	55	15	25
1467658	V102-1063-03-EX	M63x1,5	10	68	16	10