



## Screw plug Polyamide IP66 Ex e Metric

For secure sealing of unused threaded or clearance holes.

### Specification

<b>MATERIAL</b>	Polyamide PA66
<b>INGRESS PROTECTION</b>	IP66
<b>TEMPERATURE RANGE</b>	-55°C...+95°C
<b>COLOUR</b>	Black RAL 9005
<b>TEST STANDARD</b>	EN 60079-0:2012, IEC 60079-0:2011, EN 60079-7:2007, IEC 60079-7:2006, EN 60079-31:2009, IEC 60079-31:2008
<b>CATEGORY / ZONE</b>	2 G (1,2) 2 D (21,22)
<b>EQUIPMENT GROUP</b>	II
<b>TYPE OF PROTECTION</b>	Ex e IIC Gb Ex tb IIIC Db
<b>EU-TYPE CERTIFICATE</b>	PTB 98 ATEX 3130
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	CONNECTION THREAD	L MM	DA MM	H MM	SWI MM	PCS/PACK
1467503	M16x1,5	11	21	15	8	20
1467504	M20x1,5	12	25	16	8	20
1467505	M25x1,5	12	30	16	8	20
1467506	M32x1,5	14	37	19.5	8	10
1467507	M40x1,5	14	45	19.5	8	10
1467508	M50x1,5	15	55	20.5	8	5