



Cable Gland Brass IP68 blueglobe Long thread Metric

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
SEALING RING	TPE
O-RING	Nitrile Rubber NBR
INGRESS PROTECTION	IP68 - 15 bar, IP69K
TEMPERATURE RANGE	-40°C...+130°C
COLOUR	Brass nickel plated
TEST STANDARD	EN 50262
CERTIFICATIONS	VDE, UL, GL
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	CABLE Ø MM WITHOUT INLET	CABLE Ø MM WITH INLET	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1470590	BG812MS	M12x1,5	2 - 8	5,0 - 8,0	2,0 - 5,0	15	36	17	18.9	50
1470591	BG816MS	M16x1,5	4 - 11	7,0 - 11,0	4,0 - 7,0	15	40	20	22.2	50
1470592	BG820MS	M20x1,5	5 - 14	9,0 - 14,0	5,0 - 9,0	15	44	24	26.5	50
1470593	BG825MS	M25x1,5	11 - 20	16,0 - 20,0	11,0 - 16,0	15	45	30	33	50
1470594	BG832MS	M32x1,5	15 - 25	20,0 - 25,0	15,0 - 20,0	15	47	36	39.5	25
1470595	BG840MS	M40x1,5	20 - 32	26,0 - 32,0	20,0 - 26,0	15	50	45	48	10
1470596	BG850MS	M50x1,5	31 - 42	35,0 - 42,0	31,0 - 35,0	15	54	57	61	5
1470597	BG863MS	M63x1,5	41 - 54	46,0 - 54,0	41,0 - 46,0	15	55	68	72	5