



## Cable Gland Brass IP68 blueglobe Metric

### Specification

<b>MATERIAL</b>	Brass nickel plated (CuZn39Pb3)
<b>SEALING RING</b>	TPE
<b>O-RING</b>	Nitrile Rubber NBR
<b>INGRESS PROTECTION</b>	IP68 - 15 bar, IP69K
<b>TEMPERATURE RANGE</b>	-40°C....+130°C
<b>COLOUR</b>	Brass nickel plated
<b>TEST STANDARD</b>	EN 50262
<b>CERTIFICATIONS</b>	VDE, UL, GL
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	CABLE Ø MM WITHOUT INLET	CABLE Ø MM WITH INLET	L MM	H MM	SWI MM	E1 MM	PCS/PACK
-	BG20812MS/1MM	M8x1,0	3 - 6	3,0 - 6,0	-	5	27	11	12.4	50
-	BG210MS	M10x1,0	1,5 - 6	3,0 - 6,0	1,5 - 3,0	6	26	13	14.2	50
1470510	BG212MS	M12x1,5	2 - 8	5,0 - 8,0	2,0 - 5,0	5	26	17	18.9	50
1470511	BG216MS	M16x1,5	4 - 11	7,0 - 11,0	4,0 - 7,0	6	31	20	22.2	50
1470512	BG220MS	M20x1,5	5 - 14	9,0 - 14,0	5,0 - 9,0	6.5	35.5	24	26.5	50
1470513	BG225MS	M25x1,5	11 - 20	16,0 - 20,0	11,0 - 16,0	7.5	37.5	30	33	50
1470514	BG232MS	M32x1,5	15 - 25	20,0 - 25,0	15,0 - 20,0	8	40	36	39.5	25
1470515	BG240MS	M40x1,5	20 - 32	26,0 - 32,0	20,0 - 26,0	8	43	45	48	10
1470516	BG250MS	M50x1,5	31 - 42	35,0 - 42,0	31,0 - 35,0	10	49	57	61	5
1470517	BG263MS	M63x1,5	41 - 54	46,0 - 54,0	41,0 - 46,0	10	50	68	72	5
1470518	BG275MS	M75x1,5	54 - 65	58,0 - 65,0	54,0 - 58,0	15	62	81	87	5
1470519	BG285MS	M85x2,0	65 - 77	70,0 - 77,0	65,0 - 70,0	15	64	95	102	1