



Cable Gland Brass IP68 UNI Dicht 50mm long thread Metric

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
SEALING RING	TPE
O-RING	NBR
INGRESS PROTECTION	IP68 up to 10 bar
TEMPERATURE RANGE	-40°C...+130°C
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW1 MM	SW2 MM	E1 MM	E2 MM	PCS/PACK
-	22052D7/50lg	M20x1,5	4,0 - 6,5	50	71	22	22	24.4	24.4	10
-	22052D8/50lg	M20x1,5	5,0 - 8,0	50	71	22	22	24.4	24.4	10
-	22052D9/50lg	M20x1,5	6,5 - 9,5	50	71	22	22	24.4	24.4	10
-	22052D11/50lg	M20x1,5	7,0 - 10,5	50	71	22	22	24.4	24.4	10
-	22052D13/50lg	M20x1,5	9,0 - 13,0	50	71	22	22	24.4	24.4	10
-	22553D7/50lg	M25x1,5	4,0 - 6,5	50	71	28	24	31.2	26.7	10
-	22553D8/50lg	M25x1,5	5,0 - 8,0	50	71	28	24	31.2	26.7	10
-	22553D9/50lg	M25x1,5	6,5 - 9,5	50	71	28	24	31.2	26.7	10
-	22553D11/50lg	M25x1,5	7,0 - 10,5	50	71	28	24	31.2	26.7	10
-	22553D13/50lg	M25x1,5	9,0 - 13,0	50	71	28	24	31.2	26.7	10
-	22553D16/50lg	M25x1,5	11,5 - 15,5	50	71	28	24	31.2	26.7	10
-	23254D11/50lg	M32x1,5	7,0 - 10,5	50	76	35	30	38.5	33.5	5
-	23254D13/50lg	M32x1,5	9,0 - 13,0	50	76	35	30	38.5	33.5	5
-	23254D16/50lg	M32x1,5	11,5 - 15,5	50	76	35	30	38.5	33.5	5
-	23254D18/50lg	M32x1,5	14,0 - 18,0	50	76	35	30	38.5	33.5	5
-	23254D20/50lg	M32x1,5	17,0 - 20,5	50	76	35	30	38.5	33.5	5
-	24055D16/50lg	M40x1,5	11,5 - 15,5	50	79	43	40	47.3	43.5	5
-	24055D18/50lg	M40x1,5	14,0 - 18,0	50	79	43	40	47.3	43.5	5
-	24055D20/50lg	M40x1,5	17,0 - 20,5	50	79	43	40	47.3	43.5	5
-	24055D25/50lg	M40x1,5	20,0 - 25,0	50	79	43	40	47.3	43.5	5
-	24055D28/50lg	M40x1,5	24,0 - 28,0	50	79	43	40	47.3	43.5	5