



Cable Gland Brass IP68 UNI Dicht Long thread Metric

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
SEALING RING	TPE
O-RING	NBR
INGRESS PROTECTION	IP68 up to 10 bar
TEMPERATURE RANGE	-40°C...+130°C
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW1 MM	SW2 MM	E1 MM	E2 MM	PCS/PACK
N9393120	81249D7	M12x1,5	4,0 - 6,5	15	35	14	14	15.5	15.5	50
N9393121	81650D7	M16x1,5	4,0 - 6,5	15	35	18	17	20	18.9	50
N9393122	81650D8	M16x1,5	5,0 - 8,0	15	35	18	17	20	18.9	50
N9393123	81650D9	M16x1,5	6,5 - 9,5	15	35	18	17	20	18.9	50
N9393124	82052D7	M20x1,5	4,0 - 6,5	15	35	22	22	24.4	24.4	50
N9393125	82052D8	M20x1,5	5,0 - 8,0	15	35	22	22	24.4	24.4	50
N9393126	82052D9	M20x1,5	6,5 - 9,5	15	35	22	22	24.4	24.4	50
N9393127	82052D11	M20x1,5	7,0 - 10,5	15	35	22	22	24.4	24.4	50
N9393128	82052D13	M20x1,5	9,0 - 13,0	15	35	22	22	24.4	24.4	50
N9393129	82553D7	M25x1,5	4,0 - 6,5	15	36	28	24	31.2	26.7	50
N9393130	82553D8	M25x1,5	5,0 - 8,0	15	36	28	24	31.2	26.7	50
N9393131	82553D9	M25x1,5	6,5 - 9,5	15	36	28	24	31.2	26.7	50
N9393132	82553D11	M25x1,5	7,0 - 10,5	15	36	28	24	31.2	26.7	50
N9393133	82553D13	M25x1,5	9,0 - 13,0	15	36	28	24	31.2	26.7	50
N9393134	82553D16	M25x1,5	11,5 - 15,5	15	36	28	24	31.2	26.7	50
N9393135	83254D11	M32x1,5	7,0 - 10,5	15	40	35	30	38.5	33.5	25
N9393136	83254D13	M32x1,5	9,0 - 13,0	15	40	35	30	38.5	33.5	25
N9393137	83254D16	M32x1,5	11,5 - 15,5	15	40	35	30	38.5	33.5	25
N9393138	83254D18	M32x1,5	14,0 - 18,0	15	40	35	30	38.5	33.5	25
N9393139	83254D20	M32x1,5	17,0 - 20,5	15	40	35	30	38.5	33.5	25
N9393140	84055D16	M40x1,5	11,5 - 15,5	15	40	43	40	47.3	43.5	10
N9393141	84055D18	M40x1,5	14,0 - 18,0	15	40	43	40	47.3	43.5	10
N9393142	84055D20	M40x1,5	17,0 - 20,5	15	40	43	40	47.3	43.5	10
N9393143	84055D25	M40x1,5	20,0 - 25,0	15	40	43	40	47.3	43.5	10
N9393144	84055D28	M40x1,5	24,0 - 28,0	15	40	43	40	47.3	43.5	10
N9393145	85056D32	M50x1,5	27,0 - 32,0	15	43	54	50	58	53.5	5
N9393146	85056D34	M50x1,5	29,0 - 34,0	15	43	54	50	58	53.5	5
N9393147	85056D36	M50x1,5	32,0 - 36,0	15	43	54	50	58	53.5	5
N9393148	85057D40	M50x1,5	36,0 - 40,0	15	43	57	57	61	61	5
N9393149	86358D44	M63x1,5	39,0 - 44,0	15	45	68	68	74	74	5