



Cable Gland Polyamide IP68 blueglobe Metric

Specification

MATERIAL	Polyamid PA6.6 V0
SEALING RING	TPE
INGRESS PROTECTION	IP68 - 15 bar, IP69K
TEMPERATURE RANGE	-20°C...+120°C
COLOUR	Lightgrey RAL 7035
TEST STANDARD	EN 50262
CERTIFICATIONS	VDE, UL, GL
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	CABLE Ø MM WITHOUT INLET	CABLE Ø MM WITH INLET	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1470520	BG212PA	M12x1,5	2 - 7,5	5,0 - 7,5	2,0 - 5,0	8	31	17	19.5	50
1470521	BG216PA	M16x1,5	4 - 11	7,0 - 11,0	4,0 - 7,0	9	36	20	22.8	50
1470522	BG220PA	M20x1,5	5 - 14	9,0 - 14,0	5,0 - 9,0	9	42	24	27	50
1470523	BG225PA	M25x1,5	11 - 20	16,0 - 20,0	11,0 - 16,0	9	43	30	34	50
1470524	BG232PA	M32x1,5	15 - 25	20,0 - 25,0	15,0 - 20,0	11	46	36	41	25
1470525	BG240PA	M40x1,5	20 - 32	26,0 - 32,0	20,0 - 26,0	12	50	45	49.5	10
1470526	BG250PA	M50x1,5	31 - 41	35,0 - 41,0	31,0 - 35,0	15	62	57	61	5
1470527	BG263PA	M63x1,5	41 - 53	46,0 - 53,0	41,0 - 46,0	15	64	70	75	5