



Cable Gland Stainless Steel LevelEx Ex-d/Ex-e Metric

Ex-d/Ex-e for non armoured cable

The cable gland LevelEx® provides a single pull resistant seal on the outer sheath of any cable. It maintains Flameproof “Ex-d” and Increased Safety “Ex-e” methods of explosion protection, IP 66 + IP 68 (10 bar, 1 hour).

An integral o-ring seal is fitted to the connection threads as standard.

- Compact design
- IP66 and IP68 (10 bar, 1hour)
- Quick and easy installation

Specification

MATERIAL	Stainless Steel 1.4404/AISI 316L
SEALING RING	Silicone
INGRESS PROTECTION	IP66 + IP68 (10 bar, 1h)
TEMPERATURE RANGE	-60°C...+130°C
STANDARDS	Compliance: EN60079-0:2012 + A11:2013, EN 60079-1:2014 Standard: EN 60079-7:2015, EN 60079-31:2014 IEC 60079-0:2017, IEC 60079-1:2014, IEC 60079-7:2015, IEC 60079-31:2013
CERTIFICATIONS	Designation gas: II 2G Ex db eb IIC Gb Designation dust: II 2D Ex ta IIIC Da IP 66/68 Certificate No. ATEX: PTB 18 ATEX 1001X xx CE 0102 IECEX: IECEX PTB 18.0001X EAC: RU C-DE.AA71.B.00390

Variants

ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW MM	E MM	PCS/PACK
Lex216VA/316LHTS	M16x1,5	7,0 - 11,0	16	48	20	22	10
Lex220VA/316LHTS	M20x1,5	8,0 - 14,0	16	53	24	26	10
Lex225VA/316LHTS	M25x1,5	12,5 - 20,0	16	56	30	32.5	10
Lex232VA/316LHTS	M32x1,5	18,5 - 26,0	16	59	36	39	10
Lex240VA/316LHTS	M40x1,5	26,0 - 34,0	16	62.5	46	50	5
Lex250VA/316LHTS	M50x1,5	33,0 - 45,0	16	67	60	64	5
Lex263VA/316LHTS	M63x1,5	44,0 - 56,0	16	71	70	74	1