



Cable Gland Polyamide IP68 blueglobe Metric

Specification

| | |
|---------------------------|----------------------|
| MATERIAL | Polyamid PA6.6 V0 |
| SEALING RING | TPE |
| INGRESS PROTECTION | IP68 - 15 bar, IP69K |
| TEMPERATURE RANGE | -20°C...+120°C |
| COLOUR | Lightgrey RAL 7035 |
| TEST STANDARD | EN 50262 |
| CERTIFICATIONS | VDE, UL, GL |
| HALOGEN-FREE | Yes |

Variants

| E-NUMBER | ARTICLE NO. | CONNECTION THREAD | FOR CABLE Ø MM | CABLE Ø MM WITHOUT INLET | CABLE Ø MM WITH INLET | L MM | H MM | SWI MM | EI MM | PCS/PACK |
|----------|-------------|-------------------|----------------|--------------------------|-----------------------|------|------|--------|-------|----------|
| 1470520 | BG212PA | M12x1,5 | 2 - 7,5 | 5,0 - 7,5 | 2,0 - 5,0 | 8 | 31 | 17 | 19.5 | 50 |
| 1470521 | BG216PA | M16x1,5 | 4 - 11 | 7,0 - 11,0 | 4,0 - 7,0 | 9 | 36 | 20 | 22.8 | 50 |
| 1470522 | BG220PA | M20x1,5 | 5 - 14 | 9,0 - 14,0 | 5,0 - 9,0 | 9 | 42 | 24 | 27 | 50 |
| 1470523 | BG225PA | M25x1,5 | 11 - 20 | 16,0 - 20,0 | 11,0 - 16,0 | 9 | 43 | 30 | 34 | 50 |
| 1470524 | BG232PA | M32x1,5 | 15 - 25 | 20,0 - 25,0 | 15,0 - 20,0 | 11 | 46 | 36 | 41 | 25 |
| 1470525 | BG240PA | M40x1,5 | 20 - 32 | 26,0 - 32,0 | 20,0 - 26,0 | 12 | 50 | 45 | 49.5 | 10 |
| 1470526 | BG250PA | M50x1,5 | 31 - 41 | 35,0 - 41,0 | 31,0 - 35,0 | 15 | 62 | 57 | 61 | 5 |
| 1470527 | BG263PA | M63x1,5 | 41 - 53 | 46,0 - 53,0 | 41,0 - 46,0 | 15 | 64 | 70 | 75 | 5 |