



Cable Gland Polyamide IP68 V-0 Metric

M32x1,5 - M63x1,5 provided with flat sealing ring made of Chloroprene on external thread.

- Integrated anchorage
- Easy-to-install

Specification

MATERIAL	Polyamide flame-retardent
SEALING RING	Polychloroprene-Nitrile rubber CR/NBR
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-20°C...+100°C
COLOUR	Lightgrey RAL 7035
TEST STANDARD	UL 514B
FLAME PROTECTION	Glow wire test 960°C at 0,8mm wall thickness
UL / CSA-FILE	E140310
HALOGEN-FREE	Yes

Variants

ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	PCS/PACK
50.612PA/FL7035	M12x1,5	3 - 6	8	31	15	100
50.616PA/FL7035	M16x1,5	5 - 10	8	35,5	20	100
50.620PA/FL7035	M20x1,5	8 - 13	8	36	24	100
50.625PA/FL7035	M25x1,5	11 - 17	8	43	29	50
50.632PA/FL7035	M32x1,5	15 - 21	10	50	36	25
50.640PA/FL7035	M40x1,5	19 - 28	10	51	46	10
50.650PA/FL7035	M50x1,5	27 - 35	12	61,5	55	5
50.663PA/FL7035	M63x1,5	32 - 42	12	65,5	68	5