



Cable Gland Polycarbonate IP68 UNI Dicht PG

Specification

MATERIAL	Polycarbonate V-0
SEALING RING	TPE
INGRESS PROTECTION	IP68 up to 10 bar
TEMPERATURE RANGE	-20°C...+100°C
COLOUR	Lightgrey RAL 7035
CERTIFICATIONS	-
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW1 MM	SW2 MM	E1 MM	E2 MM	PCS/PACK
149PC7	149PC7	PG7/12,5	4,0 - 6,5	8	31	15	15	16,5	16,5	50
14950PC7	14950PC7	PG7/12,5	5,0 - 8,0	8,5	30,5	19	19	21,2	21,2	50
14950PC9	14950PC9	PG7/12,5	6,5 - 9,5	8,5	30,5	19	19	21,2	21,2	50
150PC7	150PC7	PG9/15,2	4,0 - 6,5	9	32	19	19	21,2	21,2	50
150PC8	150PC8	PG9/15,2	5,0 - 8,0	9	32	19	19	21,2	21,2	50
150PC9	150PC9	PG9/15,2	6,5 - 9,5	9	32	19	19	21,2	21,2	50
15051PC11	15051PC11	PG9/15,2	7,0 - 10,5	8	32	22	22	24,4	24,4	50
151PC7	151PC7	PG11/18,6	4,0 - 6,5	9	32,5	22	22	24,4	24,4	50

151PC8	151PC8	PG11/18,6	5,0 - 8,0	9	32,5	22	22	24.4	24.4	50
151PC9	151PC9	PG11/18,6	6,5 - 9,5	9	32,5	22	22	24.4	24.4	50
151PC11	151PC11	PG11/18,6	7,0 - 10,5	9	32,5	22	22	24.4	24.4	50
15152PC11	15152PC11	PG11/18,6	7,0 - 10,5	9	33	24	24	26.5	26.5	50
15152PC13	15152PC13	PG11/18,6	9,0 - 13,0	9	33	24	24	26.5	26.5	50
152PC7	152PC7	PG13,5/20,4	4,0 - 6,5	9	33	24	24	26.5	26.5	50
152PC8	152PC8	PG13,5/20,4	5,0 - 8,0	9	33	24	24	26.5	26.5	50
152PC9	152PC9	PG13,5/20,4	6,5 - 9,5	9	33	24	24	26.5	26.5	50
152PC11	152PC11	PG13,5/20,4	7,0 - 10,5	9	33	24	24	26.5	26.5	50
152PC13	152PC13	PG13,5/20,4	9,0 - 13,0	9	33	24	24	26.5	26.5	50
15253PC16	15253PC16	PG13,5/20,4	11,5 - 15,5	9	33	27	27	29.5	29.5	50
15254PC18	15254PC18	PG13,5/20,4	14,0 - 18,0	9	37	33	33	36.5	36.5	25
15254PC20	15254PC20	PG13,5/20,4	17,0 - 20,5	9	37	33	33	36.5	36.5	25
153PC7	153PC7	PG16/22,5	4,0 - 6,5	9	33	27	27	29.5	29.5	50
153PC8	153PC8	PG16/22,5	5,0 - 8,0	9	33	27	27	29.5	29.5	50
153PC9	153PC9	PG16/22,5	6,5 - 9,5	9	33	27	27	29.5	29.5	50
153PC11	153PC11	PG16/22,5	7,0 - 10,5	9	33	27	27	29.5	29.5	50
153PC13	153PC13	PG16/22,5	9,0 - 13,0	9	33	27	27	29.5	29.5	50
153PC16	153PC16	PG16/22,5	11,5 - 15,5	9	33	27	27	29.5	29.5	50
15354PC18	15354PC18	PG16/22,5	14,0 - 18,0	9	38	33	33	36.5	36.5	25
15354PC20	15354PC20	PG16/22,5	17,0 - 20,5	9	38	33	33	36.5	36.5	25
154PC11	154PC11	PG21/28,3	7,0 - 10,5	11	40	33	33	36.5	36.5	25
154PC13	154PC13	PG21/28,3	9,0 - 13,0	11	40	33	33	36.5	36.5	25
154PC16	154PC16	PG21/28,3	11,5 - 15,5	11	40	33	33	36.5	36.5	25
154PC18	154PC18	PG21/28,3	14,0 - 18,0	11	40	33	33	36.5	36.5	25
154PC20	154PC20	PG21/28,3	17,0 - 20,5	11	40	33	33	36.5	36.5	25
15455PC25	15455PC25	PG21/28,3	20,0 - 25,0	11	44	43	43	46.5	46.5	10
15455PC28	15455PC28	PG21/28,3	24,0 - 28,0	11	44	43	43	46.5	46.5	10
155PC13	155PC13	PG29/37,0	9,0 - 13,0	11	44	43	43	46.5	46.5	10
155PC16	155PC16	PG29/37,0	11,5 - 15,5	11	44	43	43	46.5	46.5	10
155PC18	155PC18	PG29/37,0	14,0 - 18,0	11	44	43	43	46.5	46.5	10
155PC20	155PC20	PG29/37,0	17,0 - 20,5	11	44	43	43	46.5	46.5	10
155PC25	155PC25	PG29/37,0	20,0 - 25,0	11	44	43	43	46.5	46.5	10
155PC28	155PC28	PG29/37,0	24,0 - 28,0	11	44	43	43	46.5	46.5	10
15556PC32	15556PC32	PG29/37,0	27,0 - 32,0	11	46	53	53	57	57	5
15556PC34	15556PC34	PG29/37,0	29,0 - 34,0	11	46	53	53	57	57	5
15556PC36	15556PC36	PG29/37,0	32,0 - 36,0	11	46	53	53	57	57	5
156PC32	156PC32	PG36/47,0	27,0 - 32,0	14	47	53	53	57	57	5
156PC34	156PC34	PG36/47,0	29,0 - 34,0	14	47	53	53	57	57	5
156PC36	156PC36	PG36/47,0	32,0 - 36,0	14	47	53	53	57	57	5

