



Cable Gland Polyamide "Fix" IP68 RAL7035 Metric

- Especially suitable for installation in applications with limited space on the inner side
- Fast and easy to install, access to the inner side is not necessary
- Integrated anchorage

Specification

| | |
|---------------------------|--|
| MATERIAL | Polyamide PA6 V-2 |
| SEALING RING | Polychloroprene-Nitrile rubber CR/NBR |
| O-RING | Nitrile-Polytetrafluorethylene rubber NBR/PTFE |
| INGRESS PROTECTION | IP68 |
| TEMPERATURE RANGE | -20°C...+100°C |
| COLOUR | Lightgrey RAL 7035 |
| HALOGEN-FREE | Yes |

Variants

| E-NUMBER | SIZE | FOR CABLE Ø MM | A MM | B MM | H MM | SW1 MM | SW2 MM | PCS/PACK |
|----------|------|----------------|-------------|-------|------|--------|--------|----------|
| 1476261 | M16 | 5 - 10 | 16,1 - 16,3 | 1 - 4 | 38,5 | 24 | 20 | 100 |
| 1476262 | M20 | 8 - 13 | 20,1 - 20,4 | 1 - 4 | 42,5 | 26 | 24 | 100 |
| 1476263 | M25 | 11 - 17 | 25,1 - 25,4 | 1 - 4 | 48 | 32 | 29 | 50 |
| 1476264 | M32 | 15 - 21 | 32,1 - 32,4 | 1 - 4 | 58,5 | 42 | 36 | 25 |