



Cable Gland Polyamide IP68 Metric Complete

NOTE! M12, M50 & M63 are NOT UL validated.

- Complete with locknut and sealing ring
- Integrated anchorage
- Easy-to-install

Specification

| | |
|---------------------------------------|--------------------|
| MATERIAL | Polyamide PA6 |
| SEALING RING | TPE |
| SEALING RING CONNECTION THREAD | PVC |
| INGRESS PROTECTION | IP68 |
| TEMPERATURE RANGE | -20°C....+100°C |
| COLOUR | Lightgrey RAL 7035 |
| UL / CSA-FILE | E186042 |

Variants

| E-NUMBER | CONNECTION THREAD | FOR CABLE Ø MM | L1 MM | L2 MM | L3 MM | PCS/PACK |
|----------|-------------------|----------------|-------|-------|-------|----------|
| 1476203 | M12x1,5 | 3 - 6,5 | 7.9 | 12.1 | 13.3 | 50 |
| 1476204 | M16x1,5 | 5 - 10 | 15.7 | 14.4 | 16.7 | 25 |
| 1476205 | M20x1,5 | 10 - 14 | 15 | 19.5 | 18.4 | 25 |
| 1476206 | M25x1,5 | 13 - 18 | 15 | 18.7 | 22.3 | 20 |
| 1476207 | M32x1,5 | 18 - 25 | 14.7 | 20.3 | 26.2 | 15 |
| 1476208 | M40x1,5 | 22 - 32 | 17.7 | 23.4 | 31.6 | 6 |
| 1476209 | M50x1,5 | 30 - 38 | 17.3 | 25.7 | 31.6 | 2 |
| 1476210 | M63x1,5 | 34 - 44 | 18.5 | 27 | 32.6 | 2 |