



Cable Gland Polyamide IP68 RAL 7001

Reducing sealing ring Metric

M32x1,5 - M63x1,5 is provided with flat sealingring made of Chloroprene on external thread.

- Reducing sealing ring (bipartite) for small cable diameter. 1476170 one-piece sealing ring.
- Integrated anchorage
- Easy-to-install

Specification

MATERIAL	Polyamide PA6 V-2
SEALING RING / INNER PART	Evoprene TPE
SEALING RING / OUTER PART	Polychloroprene-Nitrile rubber CR/NBR
INGRESS PROTECTION	IP68 - 5 bar
TEMPERATURE RANGE	-20°C...+100°C (dynamisk) -40°C (static, short term)
COLOUR	Grey RAL 7001
TEST STANDARD	EN 62444 / UL514B
VDE LICENCE	40020902
UL / CSA-FILE	E140310
SEV LICENCE	01.1135
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1476170	M12x1,5	2 - 5	8	31	15	16,5	100
1476171	M16x1,5	3 - 10	8	35,5	20	22	100
1476172	M20x1,5	5 - 13	8	36	24	26,5	100
1476173	M25x1,5	8 - 17	8	43	29	32	50
1476174	M32x1,5	12 - 21	10	50	36	40	25
1476175	M40x1,5	16 - 28	10	51	46	51	10
1476176	M50x1,5	21 - 35	12	61,5	55	60	5
1476177	M63x1,5	27 - 48	12	65,5	68	75	5