



Cable Gland Polyamide IP68 RAL 9005 Metric

M32x1,5 - M63x1,5 provided with flat sealing ring made of Chloroprene on external thread.

- Integrated anchorage
- Easy-to-install

Specification

MATERIAL	Polyamide PA6 V-2
SEALING RING	Polychloroprene-Nitrile rubber CR/NBR
INGRESS PROTECTION	IP68 - 5 bar
TEMPERATURE RANGE	-20°C....+100°C (dynamisk) -40°C (static, short term)
COLOUR	Black RAL 9005
TEST STANDARD	EN 62444 / UL514B
VDE LICENCE	40020902
UL / CSA-FILE	E140310
SEV LICENCE	01.1135
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1476121	M12x1,5	3 - 6	8	31	15	16,5	100
1476122	M16x1,5	5 - 9,5	8	35,5	20	22	100
1476123	M20x1,5	8 - 13	8	36	24	26,5	100
1476129	M20x1,5	10 - 14	8	40,5	27	29,3	50
1476124	M25x1,5	11 - 17	8	43	29	32	50
1476125	M32x1,5	15 - 21	10	50	36	40	25
1476126	M40x1,5	19 - 28	10	51	46	51	10
1476127	M50x1,5	27 - 35	12	61,5	55	60	5
1476128	M63x1,5	32 - 42	12	65,5	68	75	5