



## Cable Gland Polyamide IP68 RAL 9005 with spiral top Metric

- For movable flexible cables
- Integrated anchorage
- Easy-to-install

### Specification

<b>MATERIAL</b>	Polyamide PA6 V-2
<b>SEALING RING</b>	Polychloroprene-Nitrile rubber CR/NBR
<b>INGRESS PROTECTION</b>	IP68 - 5 bar
<b>TEMPERATURE RANGE</b>	-20°C...+100°C (dynamisk) -40°C (static, short term)
<b>COLOUR</b>	Black RAL 9005
<b>VDE LICENCE</b>	40020902
<b>UL / CSA-FILE</b>	E140310
<b>SEV LICENCE</b>	01.1135
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1476141	M12x1,5	3 - 6,5	8	63,5	15	16,3	100
1476142	M16x1,5	5 - 10	15	94,5	22	24,5	100
1476143	M20x1,5	6 - 12	11	101,5	24	26,5	50
1476144	M20x1,5	10 - 14	15	116	27	29,5	25
1476145	M25x1,5	13 - 18	15	132,5	33	36	25