



Cable Gland Polyamide IP68 PG

- Integrated anchorage
- Easy-to-install

NOTE! E-14 598 52, 55, 70 & 72 are NOT UL validated.
When assembly with locknut only use E-1465762 - 99.

Specification

MATERIAL	Polyamide PA6
SEALING RING	TPE
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-20°C...+100°C
COLOUR	Lightgrey RAL 7035
UL / CSA-FILE	E186042
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L1 MM	L2 MM	L3 MM	PCS/PACK
1459852	PG7/12,5	3 - 6	8	12.8	13.4	50
1459855	PG9/15,2	4 - 8	8.1	13.9	15.2	50
1459858	PG11/18,6	5 - 10	8.2	15.4	18.3	50
1459860	PG13,5/20,4	6 - 12	8.9	15.8	18.9	50
1459862	PG16/22,5	10 - 14	8.9	17.3	19.7	50
1459864	PG21/28,3	13 - 18	10.8	18.6	23.9	25
1459866	PG29/37,0	18 - 25	10.9	20.5	27.4	20
1459868	PG36/47,0	22 - 32	14.4	24.4	30.5	10
1459870	PG42/54,0	30 - 38	14.6	25.4	31.6	5
1459872	PG48/59,3	34 - 44	15.8	25.2	31.3	5