



## Cable Gland Polyamide IP68 RAL 9005 PG

- Integrated anchorage
- Easy-to-install

### Specification

<b>MATERIAL</b>	Polyamide PA6 V-2
<b>SEALING RING</b>	Polychloroprene-Nitrile rubber CR/NBR
<b>INGRESS PROTECTION</b>	IP68 - 5 bar
<b>TEMPERATURE RANGE</b>	-20°C...+100°C (dynamisk) -40°C (static, short term)
<b>COLOUR</b>	Black RAL 9005
<b>TEST STANDARD</b>	UL 514B
<b>UL / CSA-FILE</b>	E140310
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1459874	PG7/12,5	3 - 6,5	8	30,5	15	16,5	100
1459875	PG9/15,2	4 - 8	8	34	19	21	100
1459878	PG11/18,6	5 - 10	8	37	22	24,5	100
1459880	PG13,5/20,4	6 - 12	9	39	24	26,5	100
1459882	PG16/22,5	10 - 14	10	42,5	27	30	50
1459888	PG21/28,3	13 - 18	11	47,5	33	36	50
1459890	PG29/37,0	18 - 25	11	53	42	46	25
1459892	PG36/47,0	22 - 32	13	61	53	59	10
1459894	PG42/54,0	30 - 38	13	65	60	68	5
1459899	PG48/59,3	34 - 44	14	67	65	72	5