



## Cable Gland Polyamide IP68 RAL 9005 with spiral top PG

- For movable flexible cables
- Integrated anchorage
- Easy-to-install

### Specification

<b>MATERIAL</b>	Polyamide PA6 V-2
<b>SEALING RING</b>	Polychloroprene-Nitrile rubber CR/NBR
<b>INGRESS PROTECTION</b>	IP68 - 5 bar
<b>TEMPERATURE RANGE</b>	-20°C...+100°C (dynamisk) -40°C (static, short term)
<b>COLOUR</b>	Black RAL 9005
<b>TEST STANDARD</b>	UL 514B
<b>UL / CSA-FILE</b>	E140310
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SWI MM	E1 MM	PCS/PACK
1460002	PG7/12,5	3 - 6,5	8	63	15	16,3	100
1460004	PG9/15,2	4 - 8	8	74	19	21	100
1460006	PG11/18,6	5 - 10	8	87	22	24,5	100
1460008	PG13,5/20,4	6 - 12	9	98	24	26,5	50
1460010	PG16/22,5	10 - 14	10	112	27	29,5	25
1460012	PG21/28,3	13 - 18	11	130	33	36	25