



Cable Gland Stainless Steel IP68 blueglobe VA Metric

1.4305 / AISI 303

Specification

MATERIAL	Stainless Steel 1.4305
SEALING RING	TPE
O-RING	Silicone
INGRESS PROTECTION	IP68 - 15 bar, IP69K
TEMPERATURE RANGE	-40°C...+130°C
COLOUR	Stainless Steel
TEST STANDARD	EN 50262
CERTIFICATIONS	VDE, UL, GL

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	CABLE Ø MM WITHOUT INLET	CABLE Ø MM WITH INLET	L MM	H MM	SWI MM	E1 MM	PCS/PACK
N9420510	BG212VA	M12x1,5	2 - 8	5,0 - 8,0	2,0 - 5,0	5	26	17	18.9	50
N9420511	BG216VA	M16x1,5	4 - 11	7,0 - 11,0	4,0 - 7,0	6	31	20	22.2	50
N9420512	BG220VA	M20x1,5	5 - 14	9,0 - 14,0	5,0 - 9,0	6.5	35.5	24	26.5	50
N9420513	BG225VA	M25x1,5	11 - 20	16,0 - 20,0	11,0 - 16,0	7.5	37.5	30	33	50
N9420514	BG232VA	M32x1,5	15 - 25	20,0 - 25,0	15,0 - 20,0	8	40	36	39.5	25
N9420515	BG240VA	M40x1,5	20 - 32	26,0 - 32,0	20,0 - 26,0	8	43	45	48	10
N9420516	BG250VA	M50x1,5	31 - 42	35,0 - 42,0	31,0 - 35,0	10	49	57	60	5
N9420517	BG263VA	M63x1,5	41 - 54	46,0 - 54,0	41,0 - 46,0	10	50	68	72	5
Long thread (15mm)										
N9420520	BG812VA	M12x1,5	2 - 8	5,0 - 8,0	2,0 - 5,0	15	36	17	18.9	50
N9420521	BG816VA	M16x1,5	4 - 11	7,0 - 11,0	4,0 - 7,0	15	40	20	22.2	50
N9420522	BG820VA	M20x1,5	5 - 14	9,0 - 14,0	5,0 - 9,0	15	44	24	26.5	50
N9420523	BG825VA	M25x1,5	11 - 20	16,0 - 20,0	11,0 - 16,0	15	45	30	33	50
N9420524	BG832VA	M32x1,5	15 - 25	20,0 - 25,0	15,0 - 20,0	15	47	36	39.5	50
N9420525	BG840VA	M40x1,5	20 - 32	26,0 - 32,0	20,0 - 26,0	15	50	45	48	10
N9420526	BG850VA	M50x1,5	31 - 42	35,0 - 42,0	31,0 - 35,0	15	54	57	60	5
N9420527	BG863VA	M63x1,5	41 - 54	46,0 - 54,0	41,0 - 46,0	15	55	68	72	5
N9420518	BG275VA	M75x1,5	54 - 65	58,0 - 65,0	54,0 - 58,0	15	62	81	87	5
N9420519	BG285VA	M85x2,0	65 - 77	70,0 - 77,0	65,0 - 70,0	15	64	95	102	1